MAXHUB

Commercial Display

Model Name: ND43CMA

Taking simplicity, safety and flexibility to new levels. MAXHUB Commercial Display makes every organization more ellective and productive.







Q





Professional 4K Display

4K Resolution Anti-Glare, 25% Haze

Wireless Screen Sharing

Share your screen through MAXHUB Share app or wireless dongle

External Control

Display Control through IP or RS232 protocol

Device Management

01

Manage through cloud based MAXHUB Pivot

Built-in Speakers

2 × 16W Dual speakers

Conformal Coating

Commercial level design of hareware

Energy Saving

ErP Certified Energy Star 8.0 Certified

Commercial Display

Display			Mechanical Specification	
Screen Size (c	class)	43"	Bezel Width (L × R × T × B)	9.9 / 9.9 / 9.9 / 9.9 mm 0.39 / 0.39 / 0.39 / 0.39 inch
Diagonal		42.5" 107.9cm		0.39 / 0.39 / 0.39 / 0.39 Inch
Panel Type		VA 250/ (Anti Clara)	Product Dimension (W× H × D)	964.6 × 552.5 × 71.4 mm 37.98 × 21.75 × 2.81 inch
Haze		25% (Anti-Glare)	Deckers Dimonsion (M/, LL, D)	
Aspect Ratio Native Resolution		16:9 3840 × 2160	Package Dimension (W × H × D)	1056 × 672 × 156 mm 41.57 × 26.46 × 6.14 inch
Refresh Rate		60Hz	Product Weight (Net)	9.90 kg / 21.83 pounds
Brightness (Typ.)		500 nits	Package Weight (Gross)	13.85 kg / 30.53 pounds
Backlight Type		DLED	VESA Mount (mm)	200 × 200
Contrast Ratio		5,000:1 (Typ) 1,000,000:1 (Dynamic)	Handle	No
Viewing Angle (H × V)		178°	Power	
Response Time		6.5ms		
Life Time (Min.)		50,000 hours	Power Supply	100-240V~50/60Hz
Operation Hours (Hours / Day)		24/7	Power Consumption (Standby mode)	0.5W
Orientation		Portrait / Landscape	Power Consumption (Typical)	75W
Internal Pla	ayer		Sound	
Processor		A55 × 4	Speaker Power(Max.)	2×16W
Graphic		Mali-G52 × 2		
Memory		4G	Certification	
Storage		32G		
Operating System		MAXHUB Signage OS	Safety	IEC 62368-1
UI Resolution		4K	EMC	Class B
			ErP	Yes
Connectivi	ty		Energy Star	Yes
Input	HDMI IN × 2	2.1, 3840 × 2160 @60Hz, CEC, HDMI 1 support ARC	Feature	
	USB 2.0 × 1 USB 3.0 × 1	USB 3.0 × 1 For external peripherals	Screen Share	MAXHUB Share / Miracast / AirPlay / Chromecast
	USB Type-C × 1	Video, Audio, PD 65W, LAN Network SharingBaud	Device Management	MAXHUB Pivot
	RS232 × 1	rate 9600	Protocol Control	RS232 / IP control
	RJ45 IN × 1	10M / 100M / 1000Mbps	Special Features	Auto signal change / Built-in media player Channel memory / Auto-rotate screen
	HDMI OUT × 1	Up to 4K@60Hz, Follow HDMI IN and Type-C channel		
		Android channel do not support	Accessory Included in the package Power Cord × 1	
	AUDIO OUT × 1 SPDIF × 1	3.5mm Phone Jack PCM output format		
OPS Slot		No		HDMI Cable × 1
Wi-Fi Slot		Module slot × 1	Wi-Fi Module × 1 Remote Control × 1	
Wi-Fi		Wi-Fi 6 supported		Wall Mount × 1
		802.11ac/b/g/n/a/ax, 2.4GHz/5GHz	Optional	
Bluetooth		5.2		

Wireless Dongle (WT13)

Mobile Stand (ST41B)

Mobile Stand (ST23C)

Environmental Conditions			
Operation Temperature	0° C ~ 40° C	Warranty	
Operation Humidity	10% ~ 90%RH	Display	3 years warranty
Storage Temperature	-20°C ~ 60°C		
Storage Humidity	10% ~ 90%RH		





in https://www.linkedin.com/company/maxhub-overseas/