MAXHUB 01

# Commercial Display

Model Name: ND55CMA

Taking simplicity, safety and flexibility to new levels. MAXHUB Commercial Display makes every organization more e ective and productive.





## Professional 4K Display

4K Resolution Anti-Glare, 25% Haze



### Wireless Screen Sharing

Share your screen through MAXHUB
Share app or wireless dongle



#### **External Control**

Display Control through IP or RS232 protocol



#### Device Management

Manage through cloud based MAXHUB Pivot



## Built-in Speakers

2 × 16W Dual speakers



## **Conformal Coating**

Commercial level design of hareware



## **Energy Saving**

ErP Certified
Energy Star 8.0 Certified

Display	
Screen Size (class)	55"
Diagonal	54.6" 138.7cm
Panel Type	VA
Haze	25% (Anti-Glare)
Aspect Ratio	16:9
Native Resolution	3840 × 2160
Refresh Rate	60Hz
Brightness (Typ.)	500 nits
Backlight Type	DLED
Contrast Ratio	5,000:1 (Typ) 1,000,000:1 (Dynamic)
Viewing Angle (H × V)	178°
Response Time	6.5ms
Life Time (Min.)	50,000 hours
Operation Hours (Hours / Day)	24 / 7
Orientation	Portrait / Landscape

Internal Player	
Processor	A55 × 4
Graphic	Mali-G52 × 2
Memory	4G
Storage	32G
Operating System	MAXHUB Signage OS
UI Resolution	4K

HDMI IN × 2	2.1, 3840 × 2160 @60Hz, CEC, HDMI 1 support ARC
JSB 2.0 × 1	For system upgrades
JSB 3.0 × 1	For external peripherals
JSB Type-C × 1	Video, Audio, PD 65W,
	LAN Network Sharing Baud
RS232 × 1	rate 9600
RJ45 IN × 1	10M / 100M / 1000Mbps
HDMI OUT × 1	Up to 4K@60Hz, Follow HDMI IN and Type-C channel Android channel do not support
AUDIO OUT × 1	3.5mm Phone Jack
SPDIF × 1	PCM output format
	No
	Module slot × 1
	Wi-Fi 6 supported
	802.11ac/b/g/n/a/ax, 2.4GHz/5GHz
	ISB 2.0 × 1 ISB 3.0 × 1 ISB Type-C × 1 ISS32 × 1 ISS32 × 1 IDMI OUT × 1

Environmental Conditions	
Operation Temperature	$0^{\circ}$ C ~ $40^{\circ}$ C
Operation Humidity	10% ~ 90%RH
Storage Temperature	-20°C ~ 60°C
Storage Humidity	10% ~ 90%RH

Mechanical Specification	
Bezel Width (L × R × T × B)	9.9 / 9.9 / 9.9 mm 0.39 / 0.39 / 0.39 inch
Product Dimension (W× H × D)	1233 × 703.5 × 71.4 mm 48.54 × 27.7 × 2.81 inch
Package Dimension (W × H × D)	1332 × 819 × 156 mm 52.44 × 32.24 × 6.14 inch
Product Weight (Net)	13.40 kg / 29.54 pounds
Package Weight (Gross)	19.5 kg / 43 pounds
VESA Mount (mm)	400 × 200
Handle	No
Power	
Power Supply	100-240V~50/60Hz

Power Supply	100-240V~50/60Hz
Power Consumption (Standby mode)	0.5W
Power Consumption (Typical)	112.5W

Speaker Power(Max.)	2 × 16W
Certification	
Safety	IEC 62368-1

Safety	IEC 62368-1
EMC	Class B
ErP	Yes
Energy Star	Yes

Feature	
Screen Share	MAXHUB Share / Miracast / AirPlay / Chromecast
Device Management	MAXHUB Pivot
Protocol Control	RS232 / IP control
Special Features	Auto signal change / Built-in media player / Channel memory / Auto-rotate screen

Accessory			
Included in the pa	ackage	Power Cord × 1 HDMI Cable × 1 Wi-Fi Module × 1 Remote Control × 1 Wall Mount × 1	
Optional	Wireless Dongle (WT13)	Mobile Stand (ST41B)	Mobile Stand (ST23C)

Warranty	
Display	3 years warranty



Sound